

Ref: D604-EKS

Pot washer basket 500x600 mm + Break Tank



Your professional partner

Brand : DIAMOND



·mm (BxDxH) :667x716xh1505

·kW :6,8

·Volt : 400-230/3N 50Hz

·kg : 130

·M³ : 1,1

- Realisation "double walled".
- Loading height for trays 380 mm (plates diam. 380 mm).
- CID door (double wall) with automatic closure "Soft Contact".
- LMD mixed washing, also dishes, cutlery
- Cycles 60" - 120"-80" or continuous.
- Rotating wash and rinse arms.
- Self cleaning sprinklers.
- Stamped walls.
- Adjustable stainless steel feet (160-220 mm).
- Removable control panel.
- Pump increasing the water pressure of the network.
- Automatic filling of the tank.
- Vertical washing pump(600 liters/minute) , self draining and self cleaning.
- Check valve.
- Hot water rinse, isolated stainless steel boiler (7-12 Lit., 6 kW).
- Micro switch, when the door opens.
- Safety thermostat.
- Predisposition "liquid soap dispenser".
- Manufactured in stainless steel AISI 304.
- Delivered with: 1 generic basket.

PLUS:

- "Integrated" tank's filter in stainless steel.
- Fully "pressed" tank.
- "Peristaltic" pump dispenser for rinse product.
- CSD digital control panel (soft touch).
- EED energy saving.
- DRD accelerated preheating phase.
- DID automatic diagnostic in case of problems.
- ADD display of boiler and tank temperature (HACCP conform)
- RGD Diamond Exclusivity, ensures a constant rinsing temperature and stable pressure during all the rinsing cycle.
- BTD "Break Tank" anti-pollution device, AB type.
- NB: machines guaranteed for "osmosis" water supply.

BREAK TANK : The "break tank" is an AB type "anti-pollution" device (UK standards) 1) It prevents the tank water (with detergents) to flow back into the distribution system 2) Its pump guarantees a constant pressure during the whole rinsing, the drying and hygiene are guaranteed by a T° of 85°C... until the last drop of water!